

WALL TYPES:

- 1 3/4" HTL BRDS @ 16" OC @ 9" ST @ 5/8" GIP EACH SIDE UP TO 12" ABOVE FINISH CEILING OR 3" HT BATT INSULATION
- 2 3/4" HTL BRDS @ 16" OC @ 9" ST @ 5/8" GIP EACH SIDE TO BOTTOM OF STRUCT ABOVE UP TO 12" BATT INSULATION
- 3 3/4" HTL BRDS @ 16" OC @ 9" ST @ 5/8" GIP EACH SIDE TO BOTTOM OF FINISH CEILING AREA OF 3" HT BATT INSULATION - 1/4" RATED ASSEMBLY - GA TIES @ 48" INT
- 4 6" HTL BRDS @ 16" OC @ 9" ST @ 5/8" GIP EACH SIDE TO BOTTOM OF STRUCT ABOVE UP TO 12" BATT INSULATION
- 5 HAZARDY WENERS: EXISTING WENERS APPLIED DIRECTLY TO EXTERIOR WALL BRICK; SEE RELEVATIONS AND SPEC FOR HAZARDY WENERS. PROVIDE TYPE, COLOR, AND JOINT FILL. PROVIDE 1/4" X 1/4" X 1/4" VENEER AND THE FEET IN SOME SPACES. ATTACH TO TRIM TO MAINTAIN PRE-EXISTING 1/4" VENEER. CONCRETE WIP INSTALL PER PROJECT SPECIFICATIONS AND DETAILS TO PROVIDE WEATHER-RESISTIVE DAMPER SYSTEM. PROVIDE 1/4" X 1/4" X 1/4" VENEER AND THE FEET IN SOME SPACES. ATTACH TO TRIM TO MAINTAIN PRE-EXISTING 1/4" VENEER. PROVIDE VAPOR DAMPER AND 1/4" HTL BRDS @ 16" OC @ 9" ST @ 5/8" GIP EACH SIDE TO INTERIOR FACE OF BRU-WALL.
- 6 1.5" EXTERIOR BRICK SYSTEM PER SPECIFICATION OVER BY PROTECTED BRICK. BRICKS BRU-WALL PER PROJECT SPECIFICATIONS AND DETAILS TO CREATE A WEATHER-RESISTIVE DAMPER SYSTEM. PROVIDE 1/4" X 1/4" X 1/4" VENEER AND THE FEET IN SOME SPACES. ATTACH TO TRIM TO MAINTAIN PRE-EXISTING 1/4" VENEER. PROVIDE VAPOR DAMPER AND 1/4" HTL BRDS @ 16" OC @ 9" ST @ 5/8" GIP EACH SIDE TO INTERIOR FACE OF BRU-WALL.
- 7 4" NORMAL CMU: EXTERIOR CMU, SOFT FACED AND SHOOTING FACED CONCRETE FINISH WITH PER SPECIFICATIONS WITH REINFORCING PER STRUCTURAL. PROVIDE EXTERIOR WEATHERING AS SPECIFIED.
- 8 4" NORMAL CMU: EXTERIOR CMU, SHOOTING FACED CONCRETE FINISH WITH PER SPECIFICATIONS WITH REINFORCING PER STRUCTURAL. PROVIDE EXTERIOR WEATHERING AS SPECIFIED.
- 9 4" NORMAL CMU: EXTERIOR CMU, SHOOTING FACED CONCRETE FINISH WITH PER SPECIFICATIONS WITH REINFORCING PER STRUCTURAL.

PLAN NOTES:

- 1 GAS REPLACE RE: PUMPING FOR GAS CONNECTION COORD INQUIRY FOR INSTALLATION
- 2 DRINKING FOUNTAIN RE: PLUMBING-PROVIDE BLOCKING AS REQUIRED.
- 3 WOOD PRIVACY FENCE RE: DETAIL.
- 4 3/4" X 6" X 4" ANCHOR BARS PROVIDE TRANSFER TYPE FOLDING BEAT AND GRAB BARS PER INTERIOR ELEVATIONS.
- 5 PROVIDE VENTILATION LOUVERS AT 22' ROOF AS INDICATED ON LOWER DETAIL.
- 6 PROVIDE 1" UPGRADE WOOD TRAYED HOUSE KEEPING PAD IN TRENCH DRAIN RE: PLUMBING DETAIL.
- 7 PROVIDE 4" GROSS FRAMED CASE CURBS PER DETAIL.
- 8 12" X 12" AREA DRAIN RE: PLUMBING.
- 9 CONTINUOUS TRENCH DRAIN RE: PLUMBING.
- 10 DAYLIGHT ABOVE RE: ROOF PLAN - DETAIL.
- 11 4" EXTERIOR CONCRETE STOOD.
- 12 4" PVC GATE W/ POSTS AND HANDRAILS.
- 13 4" EXTERIOR PATIO W/ COLORED, STAMPED CONCRETE.
- 14 4" EXTERIOR SIDEWALK.
- 15 ELECTRICAL PANEL, RE: ELECTRICAL.
- 16 1/4" X 1/2" ACCESS IN GYP. BD. CEILING.
- 17 4x4 STEEL POSTS RE: STRUCTURAL.

GENERAL NOTES:

- 1 CEILING HEIGHT TO BE 9'-6" AFF. UNLESS NOTED OTHERWISE.
- 2 PROVIDE BLOCKING AS REQUIRED AT ALL FIN AND RELOCATED EQUIPMENT AND CABINETS LOCATIONS.

Project: Brooklyn  
 Project No: 101  
 Address: 1300 W. 13th Ave  
14th St  
 Date: 2/18/2016  
 Drawn By: JLH  
 Checked By: JLH  
 Revision: 0 - 03.10  
 Revision: 1 - 04.15.16  
 Revision: \_\_\_\_\_  
 Revision: \_\_\_\_\_  
 Revision: \_\_\_\_\_

A 2.0

FLOOR PLAN  
SCALE: 1/4" = 1'-0"

